UN1173 Ethyl acetate AGR, ACS, ISO, Ph.Eur.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Date of issue: 08/01/2014 Revision date: 28/09/2022 Supersedes version of: 14/10/2020 Version: 2.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	:	Substance
Trade name	:	UN1173 Ethyl acetate AGR, ACS, ISO, Ph.Eur.
Chemical name	:	ethyl acetate
IUPAC name	:	ethyl acetate
EC Index-No.	:	607-022-00-5
EC-No.	:	205-500-4
CAS-No.	:	141-78-6
REACH registration No	:	01-2119475103-46
Product code	:	ETAC-0IA
Formula	:	CH3COOC2H5

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Laboratory use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

labbox labware s.l.
Migjorn, 1
P.O. Box Barcelona (SPAIN)
08338 Premia de Dalt – SPAIN
ES
T +34 937 07 79 70 - F +34 937 909 532
info@labbox.com - www.labbox.com

1.4. Emergency telephone number

Emergency number : +34 937 077 970 (For technical information_Office Hours) In case of medical emergency phone 112 or to your local emergency number.

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2	H225
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336

Full text of H and EUH statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02 GHS07

Signal word (CLP) : Danger

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP) : P210 - Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P240 - Ground/bond container and receiving equipment.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Substance type : Mono-constituent

Name	Product identifier	%
Ethyl acetate	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5 REACH-no: 01-2119475103-46	≥ 100

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.

First-aid measures after skin contact : Gently wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause respiratory irritation. May cause headache, nausea and irritation of respiratory tract. May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Cracking of the skin.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Never give anything by mouth to an unconscious person.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	:	ABC-powder.
Unsuitable extinguishing media	:	Strong water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard	:	Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire	:	Carbon oxides (CO, CO2).

5.3. Advice for firefighters

Precautionary measures fire	:	Stop leak if safe to do so. Evacuate area.
Firefighting instructions	:	Evacuate area. Use water spray or fog for cooling exposed containers.
Protection during firefighting	:	Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	:	Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Emergency procedures	:	Avoid contact with skin, eyes and clothing. Do not breathe gas. Do not breathe vapours. Ventilate spillage area.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment	:	Collect spillage.
Methods for cleaning up	:	Take up liquid spill into absorbent material. Collect spillage. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal.
Other information	:	Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Heading 8. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	:	Ensure good ventilation of the work station. Do not breathe vapours.
Hygiene measures	:	Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	:	Take precautionary measures against static discharge.
Storage conditions	:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in a well-ventilated place. Keep container tightly closed.
Incompatible products	:	Oxidizing agent. reducing agents. Strong acids. Strong bases.

Special rules on packaging : Store in a closed container. Keep only in original container.

7.3. Specific end use(s)

Laboratory chemicals.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

UN1173 Ethyl acetate AGR, ACS, ISO, Ph.Eur. (141-78-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethyl acetate
IOEL TWA	734 mg/m³
IOEL TWA [ppm]	200 ppm
IOEL STEL	1468 mg/m³
IOEL STEL [ppm]	400 ppm
France - Occupational Exposure Limits	
Local name	Acétate d'éthyle
VME (OEL TWA)	1400 mg/m³
VME (OEL TWA) [ppm]	400 ppm
Remark	Valeurs recommandées/admises
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Ethylacetat
AGW (OEL TWA) [1]	1500 mg/m³
AGW (OEL TWA) [2]	400 ppm
Remark	DFG,Y
Portugal - Occupational Exposure Limits	
Local name	Acetato de etilo
OEL TWA [ppm]	400 ppm
Spain - Occupational Exposure Limits	
Local name	Acetato de etilo
VLA-ED (OEL TWA) [1]	1460 mg/m³
VLA-ED (OEL TWA) [2]	400 ppm
United Kingdom - Occupational Exposure Limits	
Local name	Ethyl acetate
WEL TWA [2]	200 ppm
WEL STEL (ppm)	400 ppm

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

UN1173 Ethyl acetate AGR, ACS, ISO, Ph.Eur. (141-78-6)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	1468 mg/m³
Acute - local effects, inhalation	1468 mg/m³
Long-term - systemic effects, dermal	63 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	734 mg/m³
Long-term - local effects, inhalation	734 mg/m³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	734 mg/m³
Acute - local effects, inhalation	734 mg/m³
Long-term - systemic effects,oral	4,5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	367 mg/m³
Long-term - systemic effects, dermal	37 mg/kg bodyweight/day
Long-term - local effects, inhalation	367 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	0,24 mg/l
PNEC aqua (marine water)	0,024 mg/l
PNEC aqua (intermittent, freshwater)	1,65 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	1,15 mg/kg dwt
PNEC sediment (marine water)	0,115 mg/kg dwt
PNEC (Soil)	
PNEC soil	0,148 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	0,2 g/kg food
PNEC (STP)	
PNEC sewage treatment plant	650 mg/l

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:
EN 374.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:
Safety glasses

8.2.2.2. Skin protection

Hand protection:
protective gloves

Other skin protection Materials for protective clothing		
Condition	**Material**	**Standard**
Excellent resistance:	Butyl rubber	

8.2.2.3. Respiratory protection

Respiratory protection:
Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Other information:
The present safety data sheet is consistent with the specific conditions relied on to justify the registration of the substance in accordance with Article 17 or 18 of the REACH regulation. Do not eat, drink or smoke during use. Wash hands with water as a precaution.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	Colourless.
Appearance	:	Liquid.
Molecular mass	:	88,11 g/mol
Odour	:	Fruity.
Odour threshold	:	Not available
Melting point	:	-83,6 °C Atm. press.: 1 atm Decomposition: 'no' Sublimation: 'no'
Freezing point	:	Not available
Boiling point	:	77,1 °C Atm. press.: 101,325 kPa Decomposition: 'no'
Flammability	:	Not available
Explosive limits	:	Not available
Lower explosion limit	:	2,2 vol %
Upper explosion limit	:	11,5 vol %
Flash point	:	-4 °C Atm. press.: 1 atm
Auto-ignition temperature	:	427 °C (1013 hPa)
Decomposition temperature	:	Not available
pH	:	Not available
Viscosity, kinematic	:	0,489 mm²/s 25 °C
Viscosity, dynamic	:	0,451 mPa·s Temp.: '20°C' Parameter: 'dynamic viscosity (in mPa s)'
Solubility	:	Moderately soluble in water. Soluble in ethanol. Soluble in acetone. Soluble in chloroform. Soluble in dimethyl sulfoxide. Soluble in oils/fats. Water: 8 g/100ml 25 °C
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Partition coefficient n-octanol/water (Log Pow)	:	0,68 25 °C
Vapour pressure	:	108,78 hPa (22 °C)
Vapour pressure at 50 °C	:	Not available
Critical pressure	:	38500 hPa
Density	:	900 kg/m³ (20 °C)
Relative density	:	0,9 (20 °C)
Relative vapour density at 20 °C	:	3
Relative density of saturated gas/air mixture	:	1,2

Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

Minimum ignition energy : 0,46 mJ
Relative evaporation rate (ether=1) : 2,4
Specific conductivity : 46000 pS/m 25 °C
VOC content : 100 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form explosive mixture with air.

10.2. Chemical stability

Unstable.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Protect from sunlight. Water, humidity. Air contact.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Toxic vapours are released.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

UN1173 Ethyl acetate AGR, ACS, ISO, Ph.Eur. (141-78-6)	
LD50 oral rat	6100 mg/kg
LD50 oral	4934 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 20000 mg/kg bodyweight Animal: rabbit, Animal sex: male
LC50 inhalation rat (mg/l)	58

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness.
STOT-repeated exposure : Not classified

UN1173 Ethyl acetate AGR, ACS, ISO, Ph.Eur. (141-78-6)	
LOAEL (oral, rat, 90 days)	3600 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
NOAEL (oral, rat, 90 days)	900 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)

Aspiration hazard : Not classified

UN1173 Ethyl acetate AGR, ACS, ISO, Ph.Eur. (141-78-6)	
Viscosity, kinematic	0,489 mm²/s 25 °C

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

UN1173 Ethyl acetate AGR, ACS, ISO, Ph.Eur. (141-78-6)	
LC50 - Fish [1]	230 mg/l Test organisms (species): Pimephales promelas
EC50 - Daphnia [1]	164 mg/dm3
NOEC (chronic)	2,4 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

UN1173 Ethyl acetate AGR, ACS, ISO, Ph.Eur. (141-78-6)	
Persistence and degradability	Readily biodegradable.
Biochemical oxygen demand (BOD)	0,293 g O_2/g substance
Chemical oxygen demand (COD)	1,69 g O_2/g substance
ThOD	1,82 g O_2/g substance

12.3. Bioaccumulative potential

UN1173 Ethyl acetate AGR, ACS, ISO, Ph.Eur. (141-78-6)	
BCF - Fish [1]	30
Partition coefficient n-octanol/water (Log Pow)	0,68 25 °C
Bioaccumulative potential	Low.

12.4. Mobility in soil

UN1173 Ethyl acetate AGR, ACS, ISO, Ph.Eur. (141-78-6)	
Surface tension	0,024 N/m

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Must follow special treatment according to local regulation.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

European List of Waste (LoW) code : 15 01 10* - packaging containing residues of or contaminated by dangerous substances
07 01 04* - other organic solvents, washing liquids and mother liquors

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

UN-No. (ADR) : UN 1173

UN-No. (IMDG) : UN 1173

UN-No. (IATA) : UN 1173

UN-No. (ADN) : UN 1173

UN-No. (RID) : UN 1173

14.2. UN proper shipping name

Proper Shipping Name (ADR) : ETHYL ACETATE

Proper Shipping Name (IMDG) : ETHYL ACETATE

Proper Shipping Name (IATA) : Ethyl acetate

Proper Shipping Name (ADN) : ETHYL ACETATE

Proper Shipping Name (RID) : ETHYL ACETATE

Transport document description (ADR) : UN 1173 ETHYL ACETATE, 3, II, (D/E)

Transport document description (IMDG) : UN 1173 ETHYL ACETATE, 3, II (-4°C c.c.)

Transport document description (IATA) : UN 1173 Ethyl acetate, 3, II

Transport document description (ADN) : UN 1173 ETHYL ACETATE, 3, II

Transport document description (RID) : UN 1173 ETHYL ACETATE, 3, II

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3

Danger labels (ADR) : 3

:



IMDG

Transport hazard class(es) (IMDG) : 3

Danger labels (IMDG) : 3

:



IATA

Transport hazard class(es) (IATA) : 3

Danger labels (IATA) : 3

:



ADN

Transport hazard class(es) (ADN) : 3

Danger labels (ADN) : 3

:



RID

Transport hazard class(es) (RID) : 3

Danger labels (RID) : 3

:



14.4. Packing group

Packing group (ADR) : II

Packing group (IMDG) : II

Packing group (IATA) : II

Packing group (ADN) : II

Packing group (RID) : II

14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1

Limited quantities (ADR) : 1l

Excepted quantities (ADR) : E2

Packing instructions (ADR) : P001, IBC02, R001

Mixed packing provisions (ADR) : MP19

Portable tank and bulk container instructions (ADR) : T4

Portable tank and bulk container special provisions (ADR) : TP1

Tank code (ADR) : LGBF

Vehicle for tank carriage : FL

Transport category (ADR) : 2

Special provisions for carriage - Operation (ADR) : S2, S20

Hazard identification number (Kemler No.) : 33

Orange plates :



Tunnel restriction code (ADR) : D/E

EAC code : •3YE

Transport by sea

Limited quantities (IMDG) : 1 L

Excepted quantities (IMDG) : E2

Packing instructions (IMDG)	:	P001
IBC packing instructions (IMDG)	:	IBC02
Tank instructions (IMDG)	:	T4
Tank special provisions (IMDG)	:	TP1
EmS-No. (Fire)	:	F-E
EmS-No. (Spillage)	:	S-D
Stowage category (IMDG)	:	B
Flash point (IMDG)	:	-4°C c.c.
Properties and observations (IMDG)	:	Colourless liquid with a fragrant odour. Flashpoint: -4°C c.c. Explosive limits: 2.18% to 11.5% Immiscible with water.

Air transport

PCA Excepted quantities (IATA)	:	E2
PCA Limited quantities (IATA)	:	Y341
PCA limited quantity max net quantity (IATA)	:	1L
PCA packing instructions (IATA)	:	353
PCA max net quantity (IATA)	:	5L
CAO packing instructions (IATA)	:	364
CAO max net quantity (IATA)	:	60L
ERG code (IATA)	:	3L

Inland waterway transport

Classification code (ADN)	:	F1
Limited quantities (ADN)	:	1 L
Excepted quantities (ADN)	:	E2
Carriage permitted (ADN)	:	T
Equipment required (ADN)	:	PP, EX, A
Ventilation (ADN)	:	VE01
Number of blue cones/lights (ADN)	:	1

Rail transport

Classification code (RID)	:	F1
Limited quantities (RID)	:	1L
Excepted quantities (RID)	:	E2
Packing instructions (RID)	:	P001, IBC02, R001
Mixed packing provisions (RID)	:	MP19
Portable tank and bulk container instructions (RID)	:	T4
Portable tank and bulk container special provisions (RID)	:	TP1
Tank codes for RID tanks (RID)	:	LGBF
Transport category (RID)	:	2
Colis express (express parcels) (RID)	:	CE7
Hazard identification number (RID)	:	33

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	**Applicable on**
3.	UN1173 Ethyl acetate AGR, ACS, ISO, Ph.Eur.
3(a)	UN1173 Ethyl acetate AGR, ACS, ISO, Ph.Eur.

EU restriction list (REACH Annex XVII)	
Reference code	**Applicable on**
3(b)	UN1173 Ethyl acetate AGR, ACS, ISO, Ph.Eur.
40.	UN1173 Ethyl acetate AGR, ACS, ISO, Ph.Eur.

REACH Annex XIV (Authorisation List)

UN1173 Ethyl acetate AGR, ACS, ISO, Ph.Eur. is not on the REACH Annex XIV List

REACH Candidate List (SVHC)

UN1173 Ethyl acetate AGR, ACS, ISO, Ph.Eur. is not on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

UN1173 Ethyl acetate AGR, ACS, ISO, Ph.Eur. is not subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 july 2012 concerning the export and import of hazardous chemicals.

POP Regulation (Persistent Organic Pollutants)

UN1173 Ethyl acetate AGR, ACS, ISO, Ph.Eur. is not subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Ozone Regulation (1005/2009)

Ethyl acetate is not subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

VOC Directive (2004/42)

VOC content : 100 %

Explosives Precursors Regulation (2019/1148)

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

Drug Precursors Regulation (273/2004)

Contains no substance subject to Regulation (EC) 273/2004 of the European Parliament and of the Council of 11 February 2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances.

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 1, Slightly hazardous to water (Classification according to VwVwS, Annex 1 or 2; ID No. 95).

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : The substance is not listed

SZW-lijst van mutagene stoffen : The substance is not listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : The substance is not listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : The substance is not listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : The substance is not listed

Denmark

Classification remarks	:	Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations	:	Young people below the age of 18 years are not allowed to use the product

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:	
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.