Toluene GLR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 14/06/2013 Revision date: 04/05/2026 Supersedes version of: 21/10/2022 Version: 3.5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	:	Substance
Trade name	:	Toluene GLR
Chemical name	:	toluene
IUPAC name	:	toluene
EC Index-No.	:	601-021-00-3
EC-No.	:	203-625-9
CAS-No.	:	108-88-3
REACH registration No.	:	01-2119471310-51
Product code	:	TOLN-00P
Formula	:	C7H8

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category	:	Laboratory use

1.3. Details of the supplier of the safety data sheet

Labbox Labware S.L.
Migjorn, 1
08338 Premia de Dalt, Barcelona
España
T +34 937 07 79 70, F +34 937 909 532
info@labbox.com, www.labbox.com

1.4. Emergency telephone number

Emergency number	:	+34 937 077 970 (For technical information_Office Hours) In case of medical emergency phone 112 or to your local emergency number. 24 hours a day, 7 days a week

Country/Area	Organisation	Emergency number
United Kingdom	National Poisons Information Service (Belfast Centre). Royal Victoria Hospital. Grosvenor Road BT12 6BA Belfast.	0344 892 0111 Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Reproductive toxicity, Category 2	H361d
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity – Repeated exposure, Category 2	H373
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02 GHS07 GHS08

Signal word (CLP) : Danger

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H336 - May cause drowsiness or dizziness.
H361d - Suspected of damaging the unborn child.
H373 - May cause damage to organs through prolonged or repeated exposure.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.

2.3. Other hazards

Other hazards which do not result in classification : Does not contain PBT and/or vPvB substances ≥ 0.1% evaluated according to Annex XIII of REACH.

PBT: not relevant – no registration required

SECTION 3: Composition/information on ingredients

3.1. Substances

Substance type : Mono-constituent

Name	Product identifier	%
Toluene	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3 REACH-no: 01-2119471310-51	100

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Get medical advice/attention if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Give oxygen or artificial respiration if necessary. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. Do not remove clothing if it sticks to the skin. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist.

First-aid measures after ingestion : Do NOT induce vomiting. Rinse mouth out with water. If swallowed, seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : ABC-powder.
Unsuitable extinguishing media : Strong water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard : In case of fire, corrosive gases come free.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Do not inhale vapour. Avoid contact with skin and eyes. Stop leak if safe to do so. Eliminate every possible source of ignition. Evacuate area.

For emergency responders

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material. Collect spillage. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Keep containers closed.
Precautions for safe handling : Ensure good ventilation of the work station.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.
Storage conditions : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in a well-ventilated place. Keep container tightly closed.
Storage area : Store in a well-ventilated place. Store away from heat.
Special rules on packaging : Store in a closed container. Keep only in original container.

7.3. Specific end use(s)

Laboratory chemicals.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

Toluene GLR (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Toluene
IOEL TWA	192 mg/m³
	50 ppm
IOEL STEL	384 mg/m³
	100 ppm
Remark	skin
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
France - Occupational Exposure Limits	
Local name	Toluène
VLEP 8h (OEL TWA)	76,8 mg/m³
	20 ppm
VLEP CT (OEL STEL)	384 mg/m³
	100 ppm
Remark	Valeurs règlementaires contraignantes; substance classée toxique pour la reproduction de catégorie 2; risque de pénétration percutanée
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Toluol
AGW (OEL TWA)	190 mg/m³
	50 ppm
Peak exposure limitation factor	4(II)
Remark	DFG,EU,H,Y
Regulatory reference	TRGS900
Greece - Occupational Exposure Limits	
Local name	Τολουόλιο
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
Regulatory reference	Π.Δ. 162/2007
Italy - Occupational Exposure Limits	
Local name	Toluene

Toluene GLR (108-88-3)	
OEL TWA	192 mg/m³
	50 ppm
Remark	pelle
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
Portugal - Occupational Exposure Limits	
Local name	Tolueno
OEL TWA	20 ppm
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Toluen
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
Regulatory reference	Hotărârea nr. 584/2018
Spain - Occupational Exposure Limits	
Local name	Tolueno
VLA-ED (OEL TWA)	192 mg/m³
	50 ppm
VLA-EC (OEL STEL)	384 mg/m³
	100 ppm
Remark	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante. Para más información véase el Apartado 5 de este documento), VLB® (Agente químico que tiene Valor Límite Biológico específico en este documento), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país), r (Esta sustancia tiene establecidas restricciones a la fabricación, la comercialización o el uso en los términos especificados en el “Reglamento (CE) nº 1907/2006 sobre Registro, Evaluación, Autorización y Restricción de sustancias y preparados químicos” (REACH) de 18 de diciembre de 2006 (DOUE L 369 de 30 de diciembre de 2006). Las restricciones de una sustancia pueden aplicarse a todos los usos o sólo a usos concretos. El anexo XVII del Reglamento REACH contiene la lista de todas las sustancias restringidas y especifica los usos que se han restringido).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT

Toluene GLR (108-88-3)	
Spain - Biological limit values	
BLV	0,6 mg/l Parámetro: o-Cresol - Medio: Orina - Momento de muestreo: Final de la jornada laboral - Notas: F (Fondo. El indicador está generalmente presente en cantidades detectables en personas no expuestas laboraboralmente. Estos niveles de fondo están considerados en el valor VLB) 0,05 mg/l Parámetro: Tolueno - Medio: Sangre - Momento de muestreo: Principio de la última jornada de la semana laboral 0,08 mg/l Parámetro: Tolueno - Medio: orina - Momento de muestreo: Final de la jornada laboral
United Kingdom - Occupational Exposure Limits	
Local name	Toluene
WEL TWA (OEL TWA)	191 mg/m³
	50 ppm
WEL STEL (OEL STEL)	384 mg/m³
	100 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Third edition, 2018). HSE

DNEL and PNEC

Toluene GLR (108-88-3)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	384 mg/m³
Acute - local effects, inhalation	384 mg/m³
Long-term - systemic effects, dermal	384 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	192 mg/m³
Long-term - local effects, inhalation	192 mg/m³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	226 mg/m³
Acute - local effects, inhalation	226 mg/m³
Long-term - systemic effects,oral	8,13 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	56,5 mg/m³
Long-term - systemic effects, dermal	226 mg/kg bodyweight/day
Long-term - local effects, inhalation	56,5 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	0,68 mg/l
PNEC aqua (marine water)	0,68 mg/l
PNEC aqua (intermittent, freshwater)	0,68 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	16,39 mg/kg dwt
PNEC sediment (marine water)	16,39 mg/kg dwt

Toluene GLR (108-88-3)	
PNEC (Soil)	
PNEC soil	2,89 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	13,61 mg/l

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station. Use a receptor hood for fumes/vapours.

Personal protection equipment

Personal protective equipment:
ISO 374-1. Avoid all unnecessary exposure.
Personal protective equipment symbol(s):



Eye and face protection

Eye protection:
Wear a face shield

Eye protection			
Type	**Field of application**	**Characteristics**	**Standard**
Face shield			EN 166, EN 167, EN 168

Skin protection

Skin and body protection:
Wear suitable protective clothing

Skin and body protection	
Type	**Standard**
Protective clothing	EN 1149-1, EN 1149-2, EN 1149-3, EN ISO 13982-1, EN ISO 6529, EN ISO 6530

Hand protection:
Wear protective gloves

Hand protection					
Type	**Material**	**Permeation**	**Thickness (mm)**	**Penetration**	**Standard**
Category III			0.062 mm	6 (> 480 minutes)	EN 420

Other skin protection
Materials for protective clothing:
Wear foot protection

Other skin protection Materials for protective clothing		
Condition	**Material**	**Standard**
		EN ISO 13287, EN ISO 20345, EN 13832-1

Respiratory protection

Respiratory protection:
Wear appropriate mask. Wear respiratory protection

Respiratory protection			
Device	**Filter type**	**Condition**	**Standard**
filtering face piece	with filter for vapors/gases		EN 405

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	Colourless.
Appearance	:	Transparent.
Molecular mass	:	92,14 g/mol
Odour	:	characteristic.
Odour threshold	:	Not available
Melting point	:	-95 °C Atm. press.: 1013 hPa Decomposition: 'no' Sublimation: 'no'
Freezing point	:	Not available
Boiling point	:	110,6 °C Atm. press.: 1013 hPa Decomposition: 'no'
Flammability	:	Not available
Lower explosion limit	:	1,1 Vol-%
Upper explosion limit	:	7,1 Vol-%
Flash point	:	4,4 °C Atm. press.: 1013 hPa
Auto-ignition temperature	:	480 °C
Decomposition temperature	:	Not available
pH	:	Not available
Viscosity, kinematic	:	0,646 mm²/s
Viscosity, dynamic	:	0,56 mPa·s Temp.: 'other:25.0°C' Parameter: 'dynamic viscosity (in mPa s)'
Solubility	:	Material nearly insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Partition coefficient n-octanol/water (Log Pow)	:	2,73
Vapour pressure	:	29,3 hPa Temp.: 20 °C
Vapour pressure at 50°C	:	Not available
Density	:	867 kg/m³
Relative density	:	0,867
Relative vapour density at 20°C	:	Not available
Particle characteristics	:	Not applicable

9.2. Other information

Other safety characteristics

VOC content	:	100 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable in use and storage conditions as recommended in item 7.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Direct sunlight.

10.5. Incompatible materials

Strong bases. Strong acids.

10.6. Hazardous decomposition products

On burning: release of harmful/irritant gases/vapours e.g.: carbon monoxide - carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Toluene GLR (108-88-3)	
LD50 oral rat	5580 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EU Method B.1 (Acute Toxicity (Oral)), 95% CL: 5300 - 5910
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, 95% CL: 9,63 - 20,77
LC50 Inhalation - Rat	49 mg/l

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Suspected of damaging the unborn child.
STOT-single exposure : May cause drowsiness or dizziness.
STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Toluene GLR (108-88-3)	
LOAEL (oral, rat, 90 days)	1250 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	2,355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)

Aspiration hazard : May be fatal if swallowed and enters airways.

Toluene GLR (108-88-3)	
Viscosity, kinematic	0,646 mm²/s

11.2. Information on other hazards

Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The product does not meet the criteria due to its endocrine-disrupting properties.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short–term (acute) : Not classified
Hazardous to the aquatic environment, long–term (chronic) : Harmful to aquatic life with long lasting effects.

Toluene GLR (108-88-3)	
LC50 - Fish [1]	5,5 mg/l Test organisms (species): Oncorhynchus kisutch
EC50 - Crustacea [1]	10 – 100 mg/l
EC50 72h - Algae [1]	10 – 100 mg/l
LOEC (chronic)	2,76 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0,74 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic fish	1,39 mg/l Test organisms (species): Oncorhynchus kisutch Duration: '40 d'

12.2. Persistence and degradability

Toluene GLR (108-88-3)	
Persistence and degradability	Rapidly degradable
Biodegradation	100 %

12.3. Bioaccumulative potential

Toluene GLR (108-88-3)	
BCF - Fish [1]	8,32
Partition coefficient n-octanol/water (Log Pow)	2,73

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Toluene GLR (108-88-3)
PBT: not relevant – no registration required

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : Substance(s) not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Other adverse effects : Do not discharge into drains or rivers.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Must follow special treatment according to local regulation.
European List of Waste (LoW, EC 2000/532) : 14 06 03* - other solvents and solvent mixtures

HP Code	:	HP3 - “Flammable:” – flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; – flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; – flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; – flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; – water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; – other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP5 - “Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:” waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP10 - “Toxic for reproduction:” waste which has adverse effects on sexual function and fertility in adult males and females, as well as developmental toxicity in the offspring. HP14 - “Ecotoxic:” waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

UN-No. (ADR)	:	UN 1294
UN-No. (IMDG)	:	UN 1294
UN-No. (IATA)	:	UN 1294
UN-No. (ADN)	:	UN 1294
UN-No. (RID)	:	UN 1294

14.2. UN proper shipping name

Proper Shipping Name (ADR)	:	TOLUENE
Proper Shipping Name (IMDG)	:	TOLUENE
Proper Shipping Name (IATA)	:	Toluene
Proper Shipping Name (ADN)	:	TOLUENE
Proper Shipping Name (RID)	:	TOLUENE
Transport document description (ADR) (ADR)	:	UN 1294 TOLUENE, 3, II, (D/E)
Transport document description (IMDG)	:	UN 1294 TOLUENE, 3, II (7°C c.c.)
Transport document description (IATA)	:	UN 1294 Toluene, 3, II
Transport document description (ADN)	:	UN 1294 TOLUENE, 3, II
Transport document description (RID)	:	UN 1294 TOLUENE, 3, II

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	:	3
Danger labels (ADR)	:	3
	:	

IMDG

Transport hazard class(es) (IMDG)	:	3
Danger labels (IMDG)	:	3

:



IATA

Transport hazard class(es) (IATA) : 3
Danger labels (IATA) : 3
:



ADN

Transport hazard class(es) (ADN) : 3
Danger labels (ADN) : 3
:



RID

Transport hazard class(es) (RID) : 3
Danger labels (RID) : 3
:



14.4. Packing group

Packing group (ADR) : II
Packing group (IMDG) : II
Packing group (IATA) : II
Packing group (ADN) : II
Packing group (RID) : II

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-D
Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Limited quantities (ADR) : 1l
Excepted quantities (ADR) : E2
Packing instructions (ADR) : P001, IBC02, R001
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions (ADR) : TP1
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 2
Special provisions for carriage - Operation (ADR) : S2, S20
Hazard identification number (Kemler No.) : 33

Orange plates	:	
Tunnel restriction code (ADR)	:	D/E
EAC code	:	3YE

Transport by sea

Limited quantities (IMDG)	:	1 L
Excepted quantities (IMDG)	:	E2
Packing instructions (IMDG)	:	P001
IBC packing instructions (IMDG)	:	IBC02
Tank instructions (IMDG)	:	T4
Tank special provisions (IMDG)	:	TP1
Stowage category (IMDG)	:	B
Flash point (IMDG)	:	7°C c.c.
Properties and observations (IMDG)	:	Colourless liquid with a benzene-like odour. Flashpoint: 7°C c.c. Explosive limits: 1.27% to 7%. Immiscible with water.

Air transport

PCA Excepted quantities (IATA)	:	E2
PCA Limited quantities (IATA)	:	Y341
PCA limited quantity max net quantity (IATA)	:	1L
PCA packing instructions (IATA)	:	353
PCA max net quantity (IATA)	:	5L
CAO packing instructions (IATA)	:	364
CAO max net quantity (IATA)	:	60L
ERG code (IATA)	:	3L

Inland waterway transport

Classification code (ADN)	:	F1
Limited quantities (ADN)	:	1 L
Excepted quantities (ADN)	:	E2
Carriage permitted (ADN)	:	T
Equipment required (ADN)	:	PP, EX, A
Ventilation (ADN)	:	VE01
Number of blue cones/lights (ADN)	:	1

Rail transport

Classification code (RID)	:	F1
Limited quantities (RID)	:	1L
Excepted quantities (RID)	:	E2
Packing instructions (RID)	:	P001, IBC02, R001
Mixed packing provisions (RID)	:	MP19
Portable tank and bulk container instructions (RID)	:	T4
Portable tank and bulk container special provisions (RID)	:	TP1
Tank codes for RID tanks (RID)	:	LGBF
Transport category (RID)	:	2
Colis express (express parcels) (RID)	:	CE7
Hazard identification number (RID)	:	33

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	**Applicable on**
3.	Toluene GLR
3(a)	Toluene GLR
3(b)	Toluene GLR
40.	Toluene GLR
48.	Toluene GLR

REACH Annex XIV (Authorisation List)

Not listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Not listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Not listed on the PIC list (Regulation EU 649/2012)

POP Regulation (Persistent Organic Pollutants)

Not listed on the POP list (Regulation EU 2019/1021)

Ozone Regulation (2024/590)

Not listed on the Ozone Depletion list (Regulation EU 2024/590)

Council Regulation (EC) for the control of dual-use items

Not listed on the COUNCIL REGULATION (EC) of dual-use items.

VOC Directive (2004/42)

VOC content : 100 %

Explosives Precursors Regulation (EU 2019/1148)

Not listed on the Explosives Precursors list (EU)

Drug Precursors Regulation (EC 273/2004)

Listed on the Drug Precursors list (EU)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Toluene		108-88-3	2902 30 00	Category 3		Annex I

National regulations

Denmark

Class for fire hazard : Class I-1
Store unit : 1 liter
Classification remarks : F <Flam. Liq. 2>; Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations	:	Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with it. If an employee is pregnant or breastfeeding and the person in question uses or is exposed to this product at work, the employer must always carry out a risk assessment of the work. The assessment must both deal with the dangerousness of the impact and its strength and duration. The employer's decision that a pregnant or lactating woman can perform a specific work task must therefore be made in the context of her specific working conditions. See also WEA-Guideline A.1.8-7 on the working environment of pregnant and breastfeeding workers. Listed or contains substance(s) on the Denmark - Indicative list of organic solvents present in Annex 3.4.1 of the WEA Guidance C.0.1-1: Toluene (1996) (108-88-3)

France

Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK)	:	WGK 3, Highly hazardous to water (Classification according to AwSV; ID No. 194).
VOC content	:	100 %

Netherlands

SZW-lijst van kankerverwekkende stoffen	:	The substance is not listed
SZW-lijst van mutagene stoffen	:	The substance is not listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	:	The substance is not listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	:	The substance is not listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	:	Toluene is listed

Poland

Polish National Regulations : Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).
Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797).
The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended).
Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).
Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).
Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).
The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488)
Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended).
Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141).
ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891)
Regulation of the Minister of Health of 25 August 2015 on the method of marking places, pipelines, and containers and tanks used for storing or containing hazardous substances or hazardous mixtures (J.o.L. 2015, item 1368 as amended)

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.